



12 mm Combination pH/ORP

Common menu guides reduce variability and provide step-by-step procedures for maintenance and pH/ ORP calibration. This standard ¼” and 12 mm pH/ORP sensor deliver fast and accurate measurement.

Part Number	Application	Measuring range	Reference electrode	Connector	Temperature sensor	GBP Price
08350=C=0004	High temperature	0 - 14 pH		Fixed cable	PT100	Contact Us
LZX472	WW	0 - 14 pH	Ag/AgCl	Fixed cable	None	Contact Us
LZX474		2 - 11 pH				Contact Us
LZX540		8 - 14 pH	Gel KCl/AgCl		Pt100 integrated	Contact Us
LZX583	General use	0 - 14 pH		Top68	Pt100	Contact Us
LZX587		0 - 14 pH				Contact Us
LZX596		0 - 14 pH				Contact Us
LZX604		0 - 14 pH				Contact Us
08350=C=0005	Fouling environments	0 - 12 pH		Fixed cable	PT100	Contact Us
08351=C=0000	ORP at high temperature	-1500 mV - 1500 mV		Fixed cable	PT100	Contact Us
08362=A=2000	Ultrapure water				PT100	Contact Us
363629,84380						Contact Us
368417,00000		0 - 14				Contact Us